


FEATURES

- 7 years warranty based on Ta45°C (24/7)
- EPD (Environmental Product Datasheet)
- Registered in NMD (Nationale Milieu Database, in progress)
- Wide standard range of drivers (No dim, Triac, Dali, Casambi)
- CLO (Constant Light Output, in development) & NFC (for adjustable lumen outputs) available.
- High Lm/W (3600Lm 167Lm/W)
- UGR <16 (max 3200Lm). UGR <18 (max 5650Lm)
- Long lifetime of 111.000 hrs (TM21 L80B50)
- Delivered with self-locking AMP plug for easy connection with the driver
- Extra strong housing material to prevent bending
- Recess, Surface mounting and pendant options available
- Environmental packaging (10 pcs per carton)
- Engineered in the Netherlands
- ENEC approved




LED panel B 1195x295

SPECIFICATIONS

Beam angle	84°
Color	White 9016
Fixture material	Frame - Aluminium / UGR Prisma PS
LEDs	Jufei 2835
CRI	82
IK rate	IK03
IP rate	IP44
Operating temperature	-20°C / +45°C
Safety marks	EN60598
Colour consistency	MacAdam step 3
LV Plug	Yes
Safety class	III
Warranty	7 years (within the European Union and the countries of the Free Trade Association for products delivered after 1 May 2015)
Energy class	These products contain a light source of energy efficiency class D

This luminaire contains built-in LED lamps. There are no exchangeable parts inside the luminaire. EU 874/2012


¹ In applications with a flat roof (f.i. car showrooms) the temperatures may exceed 45°C. Please ask our sales office for a special driver.



IP44

LED PANEL B 1195X295 L4CS

Max 1050 mA - CRI82



ITEM SPECIFICATIONS FOR STANDARD CURRENT SETTINGS

Description	Item code	Input	Vf	W	Lm	Lm/W	CRI (typ.)	UGR	Pf	Ripple	Inrush current	B-16A Fuse
LED panel B 1195x295 L4CS max 5200lm 3000K	321K03MW63E2	max 1050mA	34,7	36,4	5200	143	82	17,9	x	x	x	x
LED panel B 1195x295 L4CS max 5650lm 4000K	321K03MW64E2	max 1050mA	34,7	36,4	5650	155	82	18,2	x	x	x	x

The max. current for these panels is 1050mA. 650mA and 800mA are mostly used and the drivers which are available are set on both of these currents. At special request there are also drivers available in other currents.

Description	Safety class	Energy class	Expected lifespan B10 (25°C)					
			L70B10	L80B10	L90B10	L70B50	L80B50	L90B50
LED panel B 1195x295 L4CS	III	D	145.000 hrs	91.000 hrs	44.000 hrs	176.000 hrs	111.000 hrs	53.000 hrs


Description	Weight	Packaging	Dimension bulk packaging	Pallet 120x80x210cm	40Ft without pallets	20Ft without pallets
LED panel B 1195x295 L4CS	1380 gr	Bulk per 10 pcs	640x340x640mm	90 pcs	5000 pcs	2000 pcs

CHOOSE YOUR LV LUMEN OUTPUT

	mA	Vf	W	Lumen Output		Lumen / Watt		UGR		CRI	Advised PSU			
				3000K	4000K	3000K	4000K	3000K	4000K		No dim	Dali	Triac	Casambi
Special request	250	31,9	8,0	1325	1450	166	182	13,2	13,5	82	CC36W150-900	CC36W150-900	EC25CA-EIZHP	x
Special request	300	32,1	9,6	1575	1700	164	177	13,8	14,1	82	CC36W150-900	CC36W150-900	EC25CA-EIZHP	127648
Special request	350	32,2	11,3	1825	2000	162	177	14,3	14,6	82	CC36W150-900	CC36W150-900	EC25CA-EIZHP	127648
Special request	450	32,6	14,7	2325	2525	158	172	15,1	15,4	82	CC36W150-900	CC36W150-900	EC25CA-EIZHP	127648
Special request	500	32,8	16,4	2575	2800	157	171	15,5	15,8	82	CC36W150-900	CC36W150-900	EC25CA-EIZHP	127648
Special request	550	32,9	18,1	2825	3075	156	170	15,8	16,1	82	CC36W150-900	CC36W150-900	EC25CA-EIZHP	127648
Special request	600	33,1	19,9	3050	3325	154	167	16,1	16,4	82	CC36W150-900	CC36W150-900	EC25CA-EIZHP	127648
Standard	650	33,2	21,6	3325	3600	154	167	16,4	16,7	82	CC36W150-900	CC36W150-900	EC25CA-EIZHP	127648
Special request	700	33,4	23,4	3550	3850	152	165	16,6	19,9	82	CC36W150-900	CC36W150-900	EC25CA-EIZHP	127648
Standard	800	33,7	27,0	4025	4350	149	161	17,0	17,3	82	CC36W150-900	CC36W150-900	x	127648
Special request	900	34,0	30,6	4550	4950	149	162	17,5	17,8	82	CC36W150-900	CC36W150-900	x	127648
Special request	1000	34,3	34,3	5000	5425	146	158	17,8	18,1	82	127574	142045	x	127648
Standard	1050	34,7	36,4	5200	5650	143	155	17,9	18,2	82	127574	142045	x	127648

All values are measured at 230V (+/- 7%).

DIMENSIONS



Waarom staat de EC25CA-EIZHP op 700mA in de PSU lijst (pagina 3)?

En er staat daarbij dat die max 350-700mA is maar in deze tabel die ook in de prijslijst staat daar staat 250 en 300mA ook bij.

PSU (INCL. LV CABLE)



PSU 36W No dim KGP CC36W150-900 NFC*
163x30x21 mm
Exp. lifespan 100.000 hrs



PSU 36W Dali KGP CC36W150-900 NFC*
163x30x21 mm
Exp. lifespan 100.000 hrs



PSU 25W Triac Eldoled EC25CA-EIZHP
151x42x28 mm
Exp. lifespan 100.000 hrs



PSU 40W No dim TCI 127574
147x44x22 mm
Exp. lifespan 100.000 hrs



PSU 38W Dali TCI 142045 NFC*
147x44x22 mm
Exp. lifespan 100.000 hrs



PSU 38W Casambi TCI 127648 NFC*
108x44x30 mm
Exp. lifespan 100.000 hrs

Item specifications (PSU)

Driver types	Supplier name	Item code	Input	Watt	Max mA	Max Vf	Pf	Eff.	Inrush current	B-16A Fuse
PSU 36W 650mA No dim KGP + LV cable	CC36W150-900	05PY03MLMA00	220-240V AC/DC	36W	150-900	40	>0.95	88%	8,5A 16µs	59 pcs
PSU 36W 650mA Dali KGP + LV cable	CC36W150-900	05QB03MLMA00	220-240V AC/DC	36W	150-900	40	>0.95	88%	8,5A 16µs	59 pcs
PSU 38W 650mA Casambi TCI + LV cable	127648	05QA03MLMA00	220-240V AC/DC	38W	300-1050	36	0.95	>90%	5A 50µs	50 pcs
PSU 25W 700mA Triac Eldoled + LV cable	EC25CA-EIZHP	05PZ03MLMA00	220-240V AC/DC	25W	350-700	36	0.99	85%	< 40mA*s	84 pcs
PSU 36W 800mA No dim KGP + LV cable	CC36W150-900	05PU03MLMA00	220-240V AC/DC	36W	150-900	40	>0.95	88%	8,5A 16µs	59 pcs
PSU 36W 800mA Dali KGP + LV cable	CC36W150-900	05PX03MLMA00	220-240V AC/DC	36W	150-900	40	>0.95	88%	8,5A 16µs	59 pcs
PSU 38W 800mA Casambi TCI + LV cable	127648	05PW03MLMA00	220-240V AC/DC	38W	300-1050	36	0.95	>90%	5A 50µs	50 pcs
PSU 40W 1050mA No dim TCI + LV cable	127574	05LI03MLMA00	220-240V AC/DC	40W	300-1050	38	>0.95	>90%	5A 50µs	50 pcs
PSU 38W 1050mA Dali TCI + LV cable	142045	05LN03MLMA00	220-240V AC/DC	38W	150-1050	36	>0.95	>89%	5A 50µs	50 pcs
PSU 38W 1050mA Casambi TCI + LV cable	127648	05M503MLMA00	220-240V AC/DC	38W	300-1050	36	0.95	>90%	5A 50µs	50 pcs

All values are measured at 230V (+/- 7%).

*NFC INSTRUCTION VIDEO



KGP CLO in development
TCI NFC & CLO in development

Waarom staat die triac (EC25CA-EIZHP) eigenlijk op 700mA terwijl de standard (op pagina 2 en in de prijslijst pagina 16) op 650mA staat?

LV CABLE (for customer PSU, not recommended)

Description	Item code
LV Cable 0,15m AMP	6H5203BLIB02

No warranty when used with own PSU.

PLUG & PLAY CABLE SYSTEM 3/5P

A
GST18 Plug & Play Solutions (Assembled to driver)



FEATURES

- Professional 16A Plug & Play system
- 3 or 5 wire system
- Widely spread in lighting market




Item specifications (accessories)

Description	Class	Length	Item code
A1 Euro plug incl. cable	II	2.0 m	015203BL1200
A2 Schuko plug incl. cable	I	1.5 m	1C5203BLA000
A3 UK plug incl. cable	II	2.0 m	0A5203BL1200
A4 3P GST18 male incl. cable 2x0.75mm²	II	0.3 m	455203BL0000
A4 3P GST18 male incl. cable 2x0.75mm²	II	3.0 m	455203BL1500
A4 3P GST18 male incl. cable 3x0.75mm²	I	0.3 m	4A5203BL0000
A4 3P GST18 male incl. cable 3x0.75mm²	I	3.0 m	4A5203BL1500
A5 5P GST18 male 1-10V/Dali incl. cable 4x0,75mm²	II	0,3 m	655203BL0000
A5 5P GST18 male 1-10V/Dali incl. cable 4x0,75mm²	II	3,0 m	655203BL1500

Description	Class	Length	Item code
A6 BST14i male Dali incl. cable	III	0.5 m	095203BL0000
A6 BST14i male Dali incl. cable	III	3.0 m	095203BL1500
A7 3P GST18 T-splitter male incl. cable	II	0.2 m	459203BL0000
A7 3P GST18 T-splitter male incl. cable	I	0.2 m	4A9203BL0000
A8 5P GST18 T-splitter male 1-10V/Dali	I / II	x	659203BL0000
A9 BST14i T-splitter male 1-10V/Dali incl. cable	III	0,2 m	099203BL0000

DISTRIBUTOR SYSTEM 2P



FEATURES

- Basic 2,5A Plug & Play system
- 2 wire system
- Not available for Dali

Item specifications (accessories)

Description	Specification	Class	Length	Item code
B 2P Plug 0,15m *	HV 0,15m male (0,75mm²)	II	0,15 m	6J5203BL1B02
C 2P Extension cable	HV Ø7,6mm 2m m/f (0,75mm²)	II	2.0 m	6F5203BL1202
D 2P Distributor 6x + Europlug	HV Ø7,6mm 6x + cable 1m 2,5A	II	1,0 m	665203BL2502
E 2P Distributor 6x + GST18 3P	HV Ø7,6mm 6x + cable 1m 2,5A	II	1,0 m	665203BL1502

*Assembled to driver, not for Dali drivers.